

## Racing Luft-Filter-Öl (Racing Air Filter Oil)

### DESCRIPTION

Racing Air Filter Oil is a specially developed product for wetting foam air filters. Dirt particles drawn in by the engine are filtered out in the foam air filter.

### PROPERTIES

- very good adhesion
- binds sand and dust and prevents wear due to abrasion
- increases service life of the engine
- waterproof
- improves filter performance

### TECHNICAL DATA

|  |   |                         |
|--|---|-------------------------|
| Form   | : | liquid                  |
| Colour                                       | : | brown                   |
| Density at 20 °C                             | : | 0.786 g/cm <sup>3</sup> |
| Viscosity at 40 °C                           | : | 48 mm <sup>2</sup> /s   |
| Flash point                                  | : | -9 °C                   |
| Regulation on flammable<br>liquids (Germany) | : | A I                     |

### APPLICATION

Racing Air Filter Oil is suitable for use on all two-stroke and four-stroke motorbikes with air or water-cooled engines using foam air filters.

### INSTRUCTIONS

Pour Racing Air Filter Oil into a suitable container. Remove coarse contaminants from the foam air filter by knocking it out. After this, place foam air filter in the container filled with the product and thoroughly massage the air filter several times. Before installing the filter, allow it to dry out for 10 to 15 minutes.

**When working with Racing Air Filter Oil, make sure that the area is well ventilated.**

### AVAILABLE PACK SIZE

|                       |        |               |
|-----------------------|--------|---------------|
| Racing Air Filter Oil | 500 ml | Part no. 1625 |
|-----------------------|--------|---------------|

PI 01/02/01

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

