

Motorbike 4T SAE 20W-50

DESCRIPTION

Motorbike 4T SAE 20W-50 is a high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions.

PROPERTIES

- universal application
- high lubricant-film stability and excellent wear protection
- high shear and ageing stability
- outstanding cleaning and dispersion properties
- prevents black sludge
- low evaporation loss and oil consumption
- miscible with all commercially available engine oils
- suitable for wet clutches
- tested for compatibility with catalytic converters

classifications and specifications:

API SG/SJ/SL

TECHNICAL DATA

Viscosity class	:	20W-50
Density at 15 °C	:	0.89 g/cm ³
Viscosity at 40 °C	:	150 mm ² /s
Viscosity at 100°C	:	17.5 mm ² /s
Viscosity index	:	128
Flash point	:	240 °C
Pour point	:	-28 °C
ASTM colour	:	3.5

APPLICATION

Four-stroke motorbike engines.

INSTRUCTIONS

The operating instructions of the engine manufacturer must be followed.

AVAILABLE PACK SIZE

Motorbike 4T 20W-50	1 l	Part no. 1500 D-GB-I-E-P
	1 l	Part no. 2656 D-PL-H-RO-TR
	1 l	Part no. 2762 D-NL-F-GR-ARAB
	4 l	Part no. 1696 D-GB-I-E-P
	20 l	Part no. 1560
	60 l	Part no. 1561
	bulk oil l	Part no. 1684

PI 10/04/14

Our information is based on thorough research and may be considered reliable, although not legally binding.

