

## Motorbike Gear Oil 75W-140 GL5 VS

**DESCRIPTION** High-performance, fully synthetic high-pressure gear oil, manufactured from high-grade synthetic base oils and additives. Permits easy, precise gear changes even in extreme conditions, and meets the criteria for performance category API GL5. Exhibits excellent wear protection properties and optimum viscosity/temperature properties.

- PROPERTIES**
- Wide viscosity range
  - Excellent wear protection
  - Friction-reducing properties
  - Significant reduction in noise
  - Protects from rust and corrosion

Specifications and approvals:  
API GL5 LS

<b>TECHNICAL DATA</b>			
Viscosity class	: 75W-140		DIN 51512
Density at +15°C	: 0.865	g/cm <sup>3</sup>	DIN 51757
Viscosity at +40°C	: 180	mm <sup>2</sup> /s	DIN 51562
Viscosity at +100°C	: 24.5	mm <sup>2</sup> /s	DIN 51562
Viscosity index	: > 160		DIN ISO 2909
Flash point	: 220	°C	DIN ISO 2592
Pour point	: < -55	°C	DIN ISO 3016
ASTM color number	: 2		DIN 51578

**APPLICATION** For motorcycle transmissions and final drives operated under the highest load. Observe the instructions of the transmission manufacturer.

**INSTRUCTIONS** The transmission manufacturer's instructions must be followed. Mixable with mineral-base oil residues which can remain during oil changes in transmissions and drives. Optimum effect only when used alone. Can be easily disposed of with standard used oil.

**AVAILABLE PACK SIZE**

Motorbike Gear Oil 75W-140 GL5 VS	500 ml	Part no. 3072 D-GB-I-E-P
--------------------------------------	--------	--------------------------

PI 00/02/14

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

